

# ioSafe SoloPRO

## + Data Recovery Service



### The world's only business-class fireproof, waterproof hard drive



#### FIREPROOF

Protects against data loss in fire up to 1550°F,  
1/2 hour Per ASTM E119



#### WATERPROOF

Protects data from flood, full submersion, 10' depth,  
72 hours fresh or salt water



#### BUSINESS-CLASS COMPATIBILITY

eSATA provides full support for  
Windows Server and Linux



#### DATA RECOVERY SERVICES

Up to \$2500 for forensic data recovery,  
Advanced Replacement included



#### ACTIVE AIRFLOW COOLING

Ensures optimum operating temperature



#### THEFTPROOF

Built in Kensington security slot or bolt down  
with anti-theft tab



#### eSATA / USB 2.0

Data transfer up to 3Gb/s  
(for eSATA systems only)



#### USB 3.0 SUPERSPEED

Data transfer up to 5Gb/s  
(for USB 3.0 systems only)

# ioSafe SoloPRO External Hard Drive

## Product Specifications

### Operational Details

- Single 3.5 SATA disk
- Quiet forced air cooling
- Multi-platform compatibility with Mac & PC/Windows
- Microsoft Windows Server & Linux (fully supported with eSATA)
- USB 3.0 or eSATA/USB 2.0 Interface

### Disaster & Security Specifications

- Fire protection - 1550°F, 1/2 hour per ASTM E119
- Flood / Submersion protection - to 10 feet water depth, 72 hours
- Proven data protection and recovery
- Tested per UL, FCC and CE Standards
- Physical theft protection
- Cable lock or floor mount
- Kensington® Lock Compatible

### Support

- 1 Year Data Recovery Service (DRS) Standard (3 and 5 year plans available)
- 3 Year manufacturer's warranty for defects Standard (5 year available with purchase of 5 year DRS upgrade)
- Up to \$2500 included for forensic recovery service
- Advanced Replacement included for warranty/DRS exchanges
- Expedited shipping for DRS support

### Inside The Box

- ioSafe SoloPRO External Hard Drive
- USB Cable
- eSATA Cable (eSATA model only)
- Power Supply
- Owners Manual and Warranty

### Electrical

- Electrical - AC input
- Voltage: 80 ~ 264 VAC at 50/60 HZ
- Typical Power Consumption: < 25W

### System Requirements

- Intel Pentium II 350 Mhz-compatible or Mac G3 processor & greater
- USB for Microsoft Windows 7/Vista/XP, Mac OS 8.6 & greater or Linux based NAS devices
- eSATA for full support of Windows Server or Linux Server systems
- For USB 3.0 or eSATA/USB 2.0 speeds, the system must support applicable specifications
- For capacities of 3TB and higher, support may be limited to Windows 7, Server 2008, Linux and Mac

### Operating Environment

- Operating: 0-35° C (95°F)
- Non-operating: 0-1550°F, 1/2 hr per ASTM E119
- Operating Humidity: 20% - 80% (non-condensing)
- Non-operating Humidity: 100%, Full water immersion, 10 feet, 3 days.

### Physical

- Size: 5.0"W x 7.1"H x 11.0"L
- Weight: 15 lbs